

TIKI PRIMER – PS



Since 1964

Primer for Poly Sulphide Sealant

DESCRIPTION

TIKI PRIMER-PS is a specially developed product to enhance the bonding of Polysulphide sealant **TIKI SEAL** with the porous substrates such as cement, concrete, wood, fibre reinforced cement sheet, stones, bricks etc.

USES

It is used as Primer on Porous Surfaces like Concrete, Fibre Reinforced Cement Sheet, Wood, Bricks and Stone Surfaces for Sealing Substrate Pores and Promote Adhesion of **TIKI SEAL** Polysulphide Sealant with the Substrate.

ADVANTAGES

- Easily applicable by brush
- Due to its low viscosity it penetrates deeply into the substrate
- Enhances the bonding of sealant with substrates
- It remains unaffected by UV rays and weathering conditions

PROPERTIES

TECHNICAL DATA	VALUE
Nature	Single Component – Moisture Sensitive Liquid
Color	Pale Yellow to Light Brown
Specific Gravity @ 30°C	1 ± 0.05
Viscosity on Ford Cup B ₄	12 to 18 Seconds
Inter coat Interval	15 to 20 Minutes
Sealant Application Time	30 Minutes after application of Primer
Number of Coats Required	Two

SURFACE PREPARATION

The surface should be thoroughly cleaned to remove loose dust, foreign particles, rust, laitance and other contaminants.

Clean and remove oil or grease from substrate using solvents.

APPLICATION INSTRUCTIONS

On the clean and dry substrate apply **TIKI PRIMER-PS** with a standard paintbrush at the rate of 50-60 sq. ft. / lit/ coat.

Minimum two coats shall be applied on the sides of the joints surface at an interval of 30 minutes.

CLEAN-UP

Use Aromatic Solvents for cleaning equipment and tools immediately after applying **TIKI PRIMER-PS**. Dried primer has to be scrapped off using tools.

SUPPLY

TIKI PRIMER-PS is supplied in standard pack sizes of 250ml, 500ml and 1 Litre container.

STORAGE

TIKI PRIMER-PS must be stored above 5°C. Store under the shed & protect from extremes of temperature. Keep container close when not in use.

SHELF LIFE

Shelf life is 12 months when stored as above and in Original Sealed Container. Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging.

SAFETY PRECAUTIONS

As with all chemical products, care should be taken during use and storage of **TIKI PRIMER-PS** to avoid contact with eyes, mouth, skin and foodstuffs until product fully cured or dried.

Treat splashes to eyes and skin immediately. If accidentally ingested, seek immediate medical attention. Keep away from children, animals and direct sources of high temperatures, naked flame and sparks. Reseal containers after use. Do not reuse containers for storage of consumable item

Disclaimer: TIKI TAR INDUSTRIES Warrants that each of its products will be manufactured in accordance with the specifications in effect on the date of manufacture.. While TIKI TAR endeavors to ensure that information given herein is correct to the best of our knowledge, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation of information given by it.

We recommend that adequate tests be performed by you to determine if this product meet all of your requirements.

Note: Properties subject to change as per specific requirement.

TIKITAR INDUSTRIES (BARODA) LIMITED

Village Road, Bhandup (W), Mumbai - 400 078, Maharashtra, India.

T: +91 22 4126 6666, 2566 7831 | F: +91 22 2566 7830

E: tiki@tikitar.com | W: www.tikitar.com

